

Style HG02 | Clevis Hanger

Size Range: 3/4-12 | 20-300mm

Material: Carbon steel

Approvals: FM approval: 3/4-12" UL listed: 3/4-8"

Finish: Plain or Zinc Plated(Hot-Dip Galvanized optional)


Service: Recommended for the suspension of stationary ductile iron or cast-iron pipe.

Installation: Hanger rod nut above clevis must be tightened securely to assure proper hanger performance.

Adjustment: Vertical adjustment without removing pipe may be made from 1 15/16" through 3 3/16", varying with the size of the clevis. Tighten upper nut after adjustment.



Technical Data



Pipe Size	Rod Size	A	B	C	D	Width	Max Load	Approx. Wt. Ea.
In/mm	In/mm	In/mm	In/mm	In/mm	In/mm	In/mm	Lbf/N	Lbs./kg
¾	¾	2.76	1.61	0.67	0.87	610	0.22	
20	M10	70.0	41.0	17.0	22.0	2713	0.10	
1	¾	3.27	1.89	0.87	0.87	730	0.27	
25	M10	83.0	48.0	22.0	22.0	3247	0.12	
1¼	¾	3.15	1.85	0.71	0.87	730	0.26	
32	M10	80.0	47.0	18.0	22.0	3247	0.12	
1½	¾	3.54	2.09	0.79	0.87	730	0.31	
40	M10	90.0	53.0	20.0	22.0	3247	0.14	
2	¾	4.37	2.64	0.98	0.87	730	0.34	
50	M10	111.0	67.0	25.0	22.0	3247	0.15	
2½	½	5.39	4.17	1.61	1.10	1350	0.96	
65	M12	137.0	106.0	41.0	28.0	6009	0.44	
3	½	6.30	4.49	1.93	1.10	1350	1.07	
80	M12	160.0	114.0	49.0	28.0	6009	0.49	
4	¾	7.76	4.96	1.65	1.10	1430	1.32	
100	M16	197.0	126.0	42.0	28.0	6365	0.60	
5	¾	9.25	5.98	2.17	1.10	1430	1.65	
125	M16	235.0	152.0	55.0	28.0	6365	0.75	
6	¾	10.87	6.54	2.24	1.50	1940	2.68	
150	M20	276.0	166.0	57.0	38.0	8635	1.22	
8	¾	14.02	8.07	2.91	1.50	2000	3.75	
200	M20	356.0	205.0	74.0	38.0	8900	1.70	
10	¾	17.56	10.08	3.54	1.89	3600	7.74	
250	M22	446.0	256.0	90.0	48.0	16020	3.51	
12	¾	20.91	11.77	4.25	1.89	3800	11.62	
300	M22	531.0	299.0	108.0	48.0	16910	5.27	